

**BONDERITE S-ST 6930 AERO
PAINT STRIPPER
(KNOWN AS TURCO EA STRIPPER 6930)**

INTRODUCTION:

BONDERITE S-ST 6930 AERO (known as TURCO EA STRIPPER 6930) is a low odor, thixotropic paint remover activated by hydrogen peroxide. It was developed for effective stripping of such resistant finishes as epoxies, epoxy primers, polyurethanes, and similar catalyzed aircraft paints.

BONDERITE S-ST 6930 AERO paint remover offers a significant advance in paint stripper technology. It complies fully with the aircraft/aerospace NESHAP.

BONDERITE S-ST 6930 AERO can be used on aluminum, mild steel, high strength steel, cadmium plated steel and titanium when used as directed. BONDERITE S-ST 6930 AERO meets the corrosivity requirements of Federal Specification TT-R-2918A. BONDERITE S-ST 6930 AERO is not recommended for use on magnesium.

FEATURES:

- Low odor
- Faster stripping
- Safe on titanium and high strength steel
- NESHAP compliant, 0 lb/gal H.A.P.S.; <2 mm Hg V.O.C. Vapor Pressure V.O.C. 647 g/l
- Significantly lower waste disposal costs
- Can be easily treated on site (see MSDS)
- Excellent cling to vertical and overhead surfaces

USE INSTRUCTIONS:

Application: Apply a uniform coating to surface being stripped by means of non-atomizing spray. Allow sufficient time for stripper to work. Performance improves as temperature increases. Agitation with a stiff bristle brush will aid in removal of the finish. Repeat if necessary.

Removal: Squeegee off bulk of loosened paint and BONDERITE S-ST 6930 AERO, followed by high pressure water rinse.

DISPOSAL INFORMATION:

Dispose of spent remover and paint residue per local, state and regional regulations. Refer to HENKEL SURFACE TECHNOLOGIES MATERIAL SAFETY DATA SHEET for additional disposal information.



**BONDERITE S-ST 6930 AERO
PAINT STRIPPER
(KNOWN AS TURCO EA STRIPPER 6930)****PRECAUTIONARY INFORMATION:**

BONDERITE S-ST 6930 AERO contains hydrogen peroxide. Avoid contact with eyes, skin and clothing. Do not take internally. Do not spray in confined areas. Avoid prolonged breathing of vapors. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, should be worn and a **NIOSH approved** respirator equipped with a mechanical filter should be worn for mist conditions.

Store containers at a temperature between 2°C and 40°C.

Before using this product refer to container label and HENKEL SURFACE TECHNOLOGIES MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 8/2013

Henkel Corporation | 32100 Stephenson Highway | Madison Heights, MI 48071
PHONE: (248) 583-9300 | FAX: (248) 583-2976 | www.henkelna.com/

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.**

The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

